

M6800/M7200 Series Monochrome laser multifunction printer

Enjoy additional value with the 4in1 high speed printer

Get additional value from the Pantum 4in1 M6800 and M7200 series with print, copy, scan, and fax functions, high print and copy speed, auto-duplex printing, budget-saving separate drum unit and toner cartridge and class-leading memory. They can serve as ideal multifunction tools for rapidly growing and large business.







Print/Copy/Scan/Fax



Automatic duplex printing



Separate Drum and Toner



ADF Scan up to 24 ppm



Convenient to Print



SPECIFICATIONS



M6800 /M7200 Series

M7200FD Model M6800FDW M7200FDN M7200FDW Printing 30ppm(A4) / 32ppm(Letter) ¦ 33ppm(A4) / 35ppm(Letter) Print speed Resolution (print, copy, scan, fax)⁽¹⁾ Print: 1200 x 600 dpi; Copy: 600 x 600 dpi; Scan: flatbed 1200×1200dpi / ADF 600×600dpi First print out time Less than 8.5s Max. monthly volume 25000 pages Recommended monthly volume 250 to 3,000 pages Processor speed 600 MHz Memory 256 MB Copying Copy speed 30cpm(A4) / 32cpm(Letter) 33cpm(A4) / 35cpm(Letter) First copy out time FB:Less than 10s; ADF:Less than 12s 25% - 400% 700m Max.copy pages 1 - 99 pages Additional function ID copy, Receipt copy, N-up copy, Clone copy, Poster copy, Manual duplex copy, Collated copy **Scanning** Scan speed 24 ppm(A4) / 25 ppm(Letter) Max.scan size Flatbed 216 x 297 mm / ADF 216 x 356mm Scan to E-mail, PC, FTP, Scan to F-mail PC FTP Scan to E-mail, PC, FTP. Output function Scan to PC, Thumb drive Thumb drive, iOS/Android Thumb drive Thumb drive, iOS/Android Color scanning Yes **Faxing** Fax type Mono Modem speed 33.6Kbps Memory 650 pages Coded system MH/MR/MMR/JBIG Compatibility ITU-T SG3 / ECM Fax feature PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, Delayed Send, Auto Redial, Auto Receive, Auto Reduction, Mobile Fax Paper handling Paper input tray 250 pages Multipurpose tray 1 page Paper output tray 120 pages (A4/70g) Media types Plain, Thick, Thin, Transparency, Cardstock, Label, Envelope A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Media sizes Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2 Media weight Input tray: 60-105g/m² Multipurpose tray: 60-200g/m² General Dimensions (w×d×h) 415 x 365 x 350mm(16.3 x 14.4 x 13.8in) Weight (without toner cartridge) 11.39kg (25.1lb) 110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A Input voltage 220V Model: AC220-240V(-15%,+10%), 50/60Hz(±2Hz), 4.5A Printing: ≤52dB(A) Copying: ≤54dB(A) Scanning: ≤52dB(A) Standby: ≤30dB(A) Noise Windows Server2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Win8.1 / Win10 (32/64 Bit); Operating system compatibility Mac OS 10.7~10.11; Linux: Ubuntu12.04/14.04 (32/64 Bit) iOS 7.0 and above; Android 4.0 and above iOS 7.0 and above; Mobile Operating system compatibility Android 4.0 and above HI-Speed USB2.0 HI-Speed USB2.0 HI-Speed USB2.0 Net: IEEE 802.3 10/100Base-Tx Net: IEEE 802.3 HI-Speed USB2.0 Net: IEEE 802.3 Interface 10/100Base-Tx 10/100Base-Tx WiFi: IEEE 802.11b/g/n WiFi: IEEE 802.11b/g/n Supplies Cartridge style (2) Separate drum and toner TL-410E (1000 pages) Starter cartridge capacity / Drum unit lifetime TL-410 (1500 pages) / DL-410 (12000 pages) / DL-410E (9000 pages) Standard capacity toner / Drum TL-410 (1500 pages), TL-410H (3000pages) / DL-410(12000pages)

⁽¹⁾ Up to
(2) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)
Copyright ©2016 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein