

Making multifunction more convenient and affordable.

M6500 Series

Monochrome Laser Multifunction Printer





3 in 1



Fast Print and Copy Speeds



Processor Speed / Memory



20000 Page Monthly Duty Cycle



Wi-Fi Connectivity and Mobile Printing



Convenient One Step Installation



KEY **SPECIFICATIONS**



lodel	M6500	M6500N	M6500W	M6500NW
inting				
Print speed	22ppm (A4) / 23ppm (Letter)			
Resolution (print, copy & scan)(1)	1200 × 1200 dpi			
First print out time	Less than 7.8 seconds			
Processor	600 MHz			
Memory	128 MB			
Duplex mode	Manual			
Connectivity	High-speed USB 2.0	Hi-speed USB 2.0 Net: IEEE802.3 10/100Base-TX	Hi-speed USB 2.0 WiFi: IEEE 802.11b/g/n	Hi-speed USB 2.0 Net: IEEE802.3 10/100Base-TX WiFi: IEEE 802.11b/g/n
Max. monthly volume (1)	20,000 pages			
ppying				
Copy speed	22ppm (A4) / 23ppm (Letter)			
First copy out time	Less than 10 seconds			
Zoom	25% - 400%			
Max. copy pages	1 - 99 pages			
Additional function	ID copy, Receipt copy, N-up copy, Clone copy			
anning				
Scanner type	Flatbed			
Max. scan size	216 x 297mm			
Color scanning	Yes			
Output function	Scan to PC	Scan to E-mail, PC, FTF	Scan to E-mail, PC, FTP, iOS/Android	Scan to E-mail, PC, FTP, iOS/Android
aper handling			150	
Paper output capacity	150 pages			
Paper output capacity Media types	100 pages Plain, Thick, Transparency, Cardstock, Label, Envelope, Thin			
Media sizes				
media 3ize3	A4, A5, A5L, A6, JIS B5, IS0 B5, B6, Letter, Legal, Executive, Folio, Oficio, Statement, 16K, Big 16k 32K,Big 32K, No.10 envelope, Monarch envelope, DL envelope, C5 envelope, C6 envelope, ZL, Japanese Postcard, custom; Yougata4, Younaga3, Nagagata3, Yougata2			
Media weight eneral	60~163g/m²			
Operating system compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.11; Linux (ubuntu12.04/14.04); iOS 6.0 above(iOS 6.0 not included); Android 4.0 and above			
Dimensions (w \times d \times h)	417x305x244mm (16.4"×12.0"×9.6")			
Weight (with toner cartridge)	7.5Kg (16.5lb)			
Power	110V Model: AC100-127V(±10%), 50/60Hz, 6A 220V Model: AC220-240V(-15%,+10%), 50/60Hz, 3A			
Recommended temperature	10 -32°C (50°F-90°F)			
Humidity range	20 - 80%			
Energy efficiency	ENERGY STAR® 2.0 certified			
Toner cartridge (2)		D*-210 corios \$+50.ds	ard capacity toner (1,600 pa	200

⁽¹⁾ Up to
(2) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)
CoPyri⁹ht ©2016 Pantum International Limited. The information contained herein is sub^ject to chan⁹e without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.